

ZAXIS-5G series

HITACHI

Reliable solutions

# ZAXIS280



## HYDRAULIC EXCAVATOR

Model Code : ZX280-5G / ZX280LC-5G

Engine Rated Power : 132 kW (177 HP)

Operating Weight : ZX280-5G : 27 400 kg / ZX280LC-5G : 28 400 kg

Backhoe Bucket : ISO Heaped : 1.00 - 1.62 m<sup>3</sup>

# ZAXIS Empower your Vision.

A ZAXIS hallmark – industry-leading hydraulic technologies, and performance no other can beat. New ZAXIS provides reliable solutions: impressive fuel economy, swift front movements, and easy operation. You'll also find Hitachi technological prowess and expertise, such as the optimized hydraulic system and engine.

New ZAXIS features the key benefits of high quality, low fuel consumption, and high durability, all of which serve to ensure low running costs.

New ZAXIS, which is empowered by comprehensive evolution, will realize customers' visions and dreams, and pioneer your colorful future.



**Key Benefits for Low Running Costs**

- High Quality
- Low Fuel Consumption
- High Durability

## More Production with Less Fuel

Page 4-5

- 9% reduction in fuel consumption
- More fuel reduction in the ECO mode
- Swift front movements with HIOS III hydraulics
- Powerful lifting operation
- Boosted swing torque
- Enhanced power boost

## No Compromise on Operator Comfort

Page 8-9

- Comfortable operating environment
- Comfort-designed operator seat
- Robust cab
- New, easy-to-use multifunctional monitor

## Reliable Solutions, with Various Options

Page 12-13

- Varied jobs, varied options
- Recommended options

## ConSite

Page 16-17

- Automatic Data Report Service

## Pursuits of Performance and Durability

Page 6-7

- Prestige R&D and quality control
- Durable, reliable engine
- Rock-solid, durable front attachment
- Strengthened undercarriage
- Proven upperstructure

## Simplified Maintenance

Page 10-11

- Dust-proof indoor net
- Grouped remote inspection points
- Attractive, robust body
- Low life cycle costs

## Hitachi Support Chain

Page 14-15

- Remote fleet management with Global e-Service
- Parts and service



Note: The photos in this brochure show excavators with optional equipments such as rear view camera.

## More Production with Less Fuel

### 9% Reduction in Fuel Consumption

New ZAXIS is a fuel-thrifty excavator that can reduce fuel consumption by 9%, compared to the conventional ZX270-3/ZX270-3F family, thanks to the HIOS III hydraulic system and engine control system, thereby reducing CO<sub>2</sub> emissions.

### More Fuel Reduction in the ECO mode

The ECO mode, a new economical mode, can further cut fuel consumption by 7% compared to the PWR mode, without sacrificing digging speed by optimal matching of operations.



### Swift Front Movements with HIOS\* III Hydraulics

Operating speed increases with less fuel consumption thanks to the HIOS III hydraulic system, developed by industry-leading hydraulic technologies and a wealth of experience. Actuators work quickly by boom weight, without needing a regenerative circuit and pressure oil.

\*Human & Intelligent Operation System

### Rapid Arm Roll-in

Arm roll-in speed increases by combined flow from arm and boom cylinders through regenerative valves for productive excavation.

### Fast Arm Speed During Boom Lowering

Arm speed increases by boom weight during boom lowering, without needing pressure oil from a pump. That is, arm circuit flow is increased for higher arm speed, allowing for quick loading of a dump truck and positioning of the front.

### Powerful Lifting Operation

The Auto Power Lift mode, which automatically surge lifting force by 10% when needed, allows for powerful lifting of buried concrete pipes or sheathing sheets.

### Boosted Swing Torque

Allows for powerful wall cutting with the bucket, and smooth swing operation on slope.

### Enhanced Power Boost

The Power Boost mode allows the operator to surge 10% more digging force for powerful excavation by pressing its button on the control lever.




# Pursuits of Performance and Durability

## Prestige R&D and Quality Control

Hitachi has earned praise for technological prowess and product performance around the world. R&D Division has a track record – including excellent design, stress analysis expertise using CAE system, and abundant production data base. What's more, a large-scale durability test field (427 hm<sup>2</sup>) allows for a series of stringent testing of new machines.

Production Division strives to automatize production processes, including robotic welding, machining, painting, assembling and transferring.




## Durable, Reliable Engine

This engine has a track record showing impressive durability at countless tough job sites around the world.

The engine — associated with a rugged design, a direct fuel injection system and an elaborate governor — goes green, and complies with EU Stage II and US EPA Tier 2 emissions regulations.

The cooling system well keeps the engine cool. The engine cover has a wider air suction area, and radiators are arranged in parallel for efficient cooling. This parallel arrangement also facilitates their cleaning.

The ample-capacity intercooler and turbocharger help yield a whopping 132 kW (177 HP) output for higher production in shorter job schedule.



## Rock-Solid, Durable Front Attachment

The boom top and foot are reinforced with thickened high-tensile steel brackets, which incorporate steel bushings to enhance durability. Arm cylinder and boom cylinders (rod extend ends) cushion shocks at stroke ends to cut noise and extend service life.

Joint pins at the front attachment are tightly fit to reduce jolt and sound. The arm-bucket joint is protected by WC thermal spraying on its contact surfaces to reduce wear and jolt. New-type HN bushings, utilized on joint pins, retain grease inside for longer greasing intervals. A reinforced resin thrust plate, mounted on the bucket pin, helps reduce wearing noise.

## Strengthened Undercarriage

The X-beam frame is made monolithically with fewer welds for higher rigidity and durability. Track adjusters absorb impacts to crawlers. Front idlers and adjuster cylinders are integrated to increase durability. Idler brackets and travel motor brackets are both thickened for added durability.

## Proven Upperstructure

The upperstructure frame is reinforced with the proven D-section skirt to increase rigidity against damage by obstacles. A large door catch is added to reduce shocks and jolts of the cab and upperstructure.



# No Compromise on Operator Comfort

## Comfortable Operating Environment

You'll feel comfortable and confident, with plenty of leg space and excellent visibility when operating the cab. The new compact console gives more leg space. The new door pillar is shifted rearward by 70 mm to widen an entry space for easy access. A new LED room light, interlocked with the door, turns on when the door opens. The front window is easily removed and stored overhead using slide rails. The overhead window is openable for ventilation. Ample air conditioner vents are located strategically for uniform air circulation inside the cab. The control panel and control levers are arranged within easy reach of the operator. AM/FM radio and AUX port (optional) for a mobile music player are available for a long work day with less fatigue. All these designs focus on operator comfort.

## Comfort-Designed Operator Seat

The luxury cloth seat is fitted with a headrest and arm rests for operator comfort. The seat can be adjusted in multiple ways, sliding and reclining, to suit operator's size and preferences. The seat can slide rearward by 40 mm more for added leg space. An air suspension with a heat pad is optional.

## Robust Cab

The robust cab, meeting the OPG (Top Guard Level 1), protects the operator from falling objects. The pilot control shut-off lever is provided with a neutral engine start system that permits engine starting only when the pilot control shut-off lever is in Lock position.



Control panel

Large storage space



## New, Easy-to-Use Multifunction Monitor

The new multi-language, multifunction monitoring system comprises a 7-inch high-resolution color monitor and a multifunction controller. The monitor allows the operator to check varying operating variables: hydraulic oil temperature, fuel level, work mode, full-auto air conditioner, AM/FM radio, rear view monitor camera (optional), maintenance support, and attachment flow adjustment. Menu items can be selected and adjusted by a multifunction controller on the control panel. A new rear view monitor camera always displays the view behind the machine.



# Simplified Maintenance



## Dust-Proof Indoor Net

A dust-proof indoor net, provided at the front of radiator, can be easily removed and cleaned with compressed air. At the rear of the radiator, air blowing can be done through a one-touch open cover. The air condenser is openable for easy cleaning at its rear.

## Attractive, Robust Body

Side frame tops of the undercarriage are sloped to let muck slide away. Track adjuster greasing ports are repositioned for easier lubrication, and well protected from muck packing.



The photo shows an excavator with an optional front glass lower guard.

## Grouped Remote Inspection Points

Service points are concentrated inside left and right covers that are readily accessible from ground level for convenient servicing and inspection, including water draining from the fuel tank, replenishment of coolant, and replacement of filters. The fuel tank is anti-corrosion coated on its inside, and has a large cleaning port at the bottom. These wise designs effectively keep fuel clean, and ease servicing. Handrails are provided at convenient locations for easy riding on the upperstructure. Plenty slip-resistant plates are located for safe maintenance.



Grouped remote filters and inspection points


Utility space and radiators



Fuel tank water drainage cock

## Low Life Cycle Costs

Service intervals are long enough to slash maintenance costs.



Lubricant Consumables

Note: Periodic inspection is required to check oil contamination and likes.

# Reliable Solutions, with Various Options



## Easy-to-Use Attachments


The operator can change over valves, adjust extra circuit flow, and check settings from the multifunctional monitor next to the operator seat. What's more, 11 jobs, including flow rate setting, can easily be selected by their identified names.

## Easy-to-Operate Breaker

When using a breaker that requires frequent change of hydraulic oil and filters, an extra hour meter on the multifunctional monitor displays operating hours of the breaker, suggesting adequate replacement timing of oil and filters. The Breaker Alarm (optional) displays an alert mark on the monitor screen, and sounds when the breaker works continuously over one minute.

## Varied Jobs, Varied Options

Lower cab front guard is provided for protection against debris during demolition and breaker operation. High-performance filters and in-line filters are available at tough job sites.



## Recommended Options




# Hitachi Support Chain

Hitachi Support Chain is a full customer support system offered after buying a Hitachi machine.

## Remote Fleet Management with Global e-Service

### Easy Access to On-Site Machines through the Internet

This on-line fleet management system allows you to access each on-site machine from a PC in your office. You can get its operating information and location to increase productivity of the fleet and reduce downtime. Operating data and log are sent to a Hitachi server for processing, and then to customer and dealers around the world. This system is available 24 hours a day, all the year around.



Note: In Some Regions, Global e-Service Is Not Available by Local Regulations.


### Main Features of Global e-Service

#### Functions

Global e-Service provides easy access to a machine on site, conveying operating information and log, including daily operating hours, fuel level, temperatures, pressures, and likes.

#### Maintenance

Maintenance data and log are displayed on a easy-to-read monitor screen, suggesting recommended maintenance for efficient fleet management.



## Parts and Service

Hitachi full customer support is available every area on the globe for full customer satisfaction through Hitachi local dealers.

### Parts

Hitachi Global Online Network, a parts supply system, is linked with Japan Parts Center, overseas depots and over 150 dealers abroad to deliver on-line parts information, including in-stock parts, order receptions, shipments and delivery period of over one million parts and components.

#### Genuine Hitachi Parts

Genuine Hitachi parts, meeting Hitachi stringent quality standards, are guaranteed according to Hitachi warranty standards. The use of genuine Hitachi parts, including engine, fuel, hydraulic oil and filters, may slash running costs, and extend machine life.

#### Ground Engaging Tools (GETs)

Hitachi provides an array of Hitachi Ground Engaging Tools developed and built for a variety of applications. Using high-

quality, well-maintained GETs will help you get customers' trust.

Note: Some dealers do not handle Hitachi GETs.

#### Remanufactured Components

Hitachi components are remanufactured according to the stringent remanufacturing standards at four factories around the world. They have high quality equivalent to new ones, and backed up by Hitachi warranty system.

Note: Some dealers do not handle Hitachi Remanufactured Components.

### Service

#### Extended Warranty – HELP

Hitachi Standard Warranty System is available on all new Hitachi machines. In addition, Hitachi offers Hitachi Extended Life Programs (HELPS) to suit customer expectations –

protecting machines under tough operating conditions, avoiding unexpected downtime, and reducing repair costs.

Note: Warranty conditions vary by equipment.

#### Diagnostic Tools – Maintenance Pro

Electronic control system needs quick on-site solutions, apart from mechanical repairs. Hitachi's Maintenance Pro can diagnose machine failures in a short time by plugging a PC into a failed machine.


#### Technical Training

On-site servicing matters despite locations to keep the machine at peak performance and reduce downtime. Technical Training Center (TTC), located in Japan, educates and trains service technicians and service support personnel coming from Hitachi dealers and factories on the globe according to the international training programs.

# ConSite

ConSite is an automatic Data Report Service that sends a monthly e-mail summarising the information from Global e-Service for each of your Hitachi machines.

Available in more than 30 languages, ConSite includes a detailed analysis of the operational data, ratios and hours. This Monthly Report is also stored on the Owner's Site for ease of reference.



## A remote fleet monitoring system to improve overall performance

### ConSite

Our ConSite Data Report Service sends you a monthly e-mail to summarise the information available on Global e-Service for each of your Hitachi machines. It includes a detailed analysis of operational data, ratios and hours, so you can see how productive and efficient your machines have been in the past month. All the information from the report is stored in the Owner's Site as well, for easy reference.

Further into the ConSite Report, you'll see non-operation and swing efficiency ratings and ratios. These compare the machine's performance against the same model class from all Hitachi owners in your region.

The monthly and total number of hours are divided for front, swing, travel and attachment operations. This will help you to determine the actual usage of your machine and maintenance planning. The monthly analysis of these variables is compared to the total lifetime of the machine in a user-friendly chart. A line graph shows the actual and projected number of hours, which helps you to manage maintenance requirements.

ConSite can also help you in the unlikely event of a fault. It will send you and your authorised Hitachi dealer an Emergency Alarm Report, so you can both respond quickly in order to minimise unscheduled downtime.

We created ConSite to improve your business operations, and enable you to analyze the productivity and efficiency of your equipment. The information it provides on machine usage is intended to help you with maintenance planning and also promotes proactive support from your dealer. Ultimately, it provides you with confidence in your Hitachi construction equipment and peace of mind to focus on other areas of your business.

### Owner's Site

You can find out all you need to know about your fleet of Hitachi construction machinery in the field from the comfort of your home or office, thanks to Owner's Site. This online management tool, available at [www.globaleservice.com](http://www.globaleservice.com), is user-friendly and offers extensive and detailed information on your Hitachi Zaxis Excavators and ZW Wheel Loaders.

The data is displayed in a flexible layout, so you can create machine groups per job site or select relevant information, depending on your requirements. As every project is different, you can customize the Owner's Site Dashboard to view data quickly and easily.



Scan this code for our ConSite function explanation & case study video

**ConSite**  
Consolidated Solution for Construction Sites

### Key Features

- Check each of your machines from your office – 24/7
- Have a remote insight into fuel consumption
- Check the current and previous locations and movements of your machine(s)
- See maintenance status and items due for renewal on each of your machines
- Receive e-mail notifications for any machine alerts, unexpected movements and so on

# SPECIFICATIONS

## ENGINE

|                        |   |
|------------------------|---|
| Model .....            | Isuzu CC-6BG1T                                    |
| Type .....             | 4-cycle water-cooled, direct injection            |
| Aspiration .....       | Turbocharged, intercooled                         |
| No. of cylinders ..... | 6   |
| Rated power            |   |
| ISO 9249, net .....    | 132 kW (177 HP) at 2 150 min <sup>-1</sup> (rpm)  |
| SAE J1349, net .....   | 132 kW (177 HP) at 2 150 min <sup>-1</sup> (rpm)  |
| Maximum torque .....   | 637 Nm (65 kgfm) at 1 800 min <sup>-1</sup> (rpm) |
| Piston displacement .. | 6.494 L   |
| Bore and stroke .....  | 105 mm x 125 mm                                   |
| Batteries .....        | 2 x 12 V / 88 Ah                                  |

## HYDRAULIC SYSTEM

### Hydraulic Pumps

|                     |  |
|---------------------|--|
| Main pumps .....    | 2 variable displacement axial piston pumps |
| Maximum oil flow .. | 2 x 236 L/min                              |
| Pilot pump .....    | 1 gear pump                                |
| Maximum oil flow .. | 34.0 L/min                                 |

### Hydraulic Motors

|              |   |
|--------------|---|
| Travel ..... | 2 variable displacement swash plate piston motors |
| Swing .....  | 1 swash plate piston motor                        |

### Relief Valve Settings

|                         |                                     |
|-------------------------|-------------------------------------|
| Implement circuit ..... | 34.3 MPa (350 kgf/cm <sup>2</sup> ) |
| Swing circuit .....     | 32.4 MPa (330 kgf/cm <sup>2</sup> ) |
| Travel circuit .....    | 34.8 MPa (355 kgf/cm <sup>2</sup> ) |
| Pilot circuit .....     | 3.9 MPa (40 kgf/cm <sup>2</sup> )   |
| Power boost .....       | 38.0 MPa (388 kgf/cm <sup>2</sup> ) |

### Hydraulic Cylinders

|        | Quantity | Bore   | Rod diameter |
|--------|----------|--------|--------------|
| Boom   | 2        | 135 mm | 95 mm        |
| Arm    | 1        | 150 mm | 105 mm       |
| Bucket | 1        | 135 mm | 90 mm        |

## UPPERSTRUCTURE

### Revolving Frame

D-section frame skirt for resistance to deformation.

### Swing Device

Swash plate piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row. Swing parking brake is spring-set/hydraulic-released disc type.

|                    |                              |
|--------------------|------------------------------|
| Swing speed .....  | 10.3 min <sup>-1</sup> (rpm) |
| Swing torque ..... | 90.5 kNm (9 200 kgfm)        |

### Operator's Cab

Independent spacious cab, 1 005 mm wide by 1 675 mm high, conforming to ISO\* Standards.

\* International Organization for Standardization

## UNDERCARRIAGE

### Tracks

Heat-treated connecting pins with dirt seals. Hydraulic (grease) track adjusters with shock-absorbing recoil springs.

### Numbers of Rollers and Shoes on Each Side

|                     |                                  |
|---------------------|----------------------------------|
| Upper rollers ..... | 2                                |
| Lower rollers ..... | 7 : ZX280-5G<br>8 : ZX280LC-5G   |
| Track shoes .....   | 45 : ZX280-5G<br>48 : ZX280LC-5G |
| Track guard .....   | 1 : ZX280-5G/ZX280LC-5G          |

### Travel Device

Each track driven by 2-speed axial piston motor. Parking brake is spring-set/hydraulic-released disc type. Automatic transmission system: High-Low.

|                     |   |
|---------------------|---|
| Travel speeds ..... | High : 0 to 5.2 km/h<br>Low : 0 to 3.1 km/h |
|---------------------|---|

Maximum traction force .. 246 kN (24 600 kgf)

Gradeability .....

70% (35 degree) continuous

## SERVICE REFILL CAPACITIES

|                                 |         |
|---------------------------------|---------|
| Fuel tank .....                 | 510.0 L |
| Engine coolant .....            | 26.0 L  |
| Engine oil .....                | 25.0 L  |
| Swing device .....              | 11.7 L  |
| Travel device (each side) ..... | 9.2 L   |
| Hydraulic system .....          | 290.0 L |
| Hydraulic oil tank .....        | 156.0 L |

## WEIGHTS AND GROUND PRESSURE


### Operating weight and Ground pressure

| Shoe type      | Shoe width | Arm length | ZX280-5G <sup>*1</sup> |                           | ZX280LC-5G <sup>*1</sup> |                           |
|----------------|------------|------------|------------------------|---------------------------|--------------------------|---------------------------|
|                |            |            | kg                     | kPa(kgf/cm <sup>2</sup> ) | kg                       | kPa(kgf/cm <sup>2</sup> ) |
| Triple grouser | 600 mm     | 2.42 m     | 27 300                 | 55 (0.56)                 | 28 300                   | 53 (0.54)                 |
|                |            | 3.11 m     | 27 400                 | 55 (0.56)                 | 28 400                   | 53 (0.54)                 |
|                |            | 3.76 m     | 27 500                 | 55 (0.56)                 | 28 500                   | 53 (0.54)                 |
|                | 700 mm     | 2.42 m     | 27 900                 | 48 (0.49)                 | 28 700                   | 46 (0.47)                 |
|                |            | 3.11 m     | 27 900                 | 48 (0.49)                 | 28 800                   | 46 (0.47)                 |
|                |            | 3.76 m     | 28 000                 | 48 (0.49)                 | 28 800                   | 46 (0.47)                 |
|                | 800 mm     | 2.42 m     | 28 200                 | 42 (0.43)                 | 29 100                   | 41 (0.42)                 |
|                |            | 3.11 m     | 28 300                 | 43 (0.44)                 | 29 100                   | 41 (0.42)                 |
|                |            | 3.76 m     | 28 400                 | 43 (0.44)                 | 29 200                   | 41 (0.42)                 |
| 900 mm         | 2.42 m     | 28 600     | 38 (0.39)              | 29 400                    | 36 (0.37)                |                           |
|                | 3.11 m     | 28 700     | 38 (0.39)              | 29 500                    | 37 (0.38)                |                           |
|                | 3.76 m     | 28 800     | 38 (0.39)              | 29 600                    | 37 (0.38)                |                           |
| Triangular     | 900 mm     | 2.42 m     | 28 900                 | 38 (0.39)                 | 29 700                   | 36 (0.37)                 |
|                |            | 3.11 m     | 28 900                 | 38 (0.39)                 | 29 800                   | 36 (0.37)                 |
|                |            | 3.76 m     | 29 000                 | 38 (0.39)                 | 29 900                   | 37 (0.38)                 |
| Flat           | 600 mm     | 2.42 m     | 28 200                 | 57 (0.58)                 | 29 000                   | 54 (0.55)                 |
|                |            | 3.11 m     | 28 200                 | 57 (0.58)                 | 29 100                   | 54 (0.55)                 |
|                |            | 3.76 m     | 28 300                 | 57 (0.58)                 | 29 100                   | 54 (0.55)                 |

\*1 :Including 1.10 m<sup>3</sup> (ISO heaped) bucket weight (900 kg) and counterweight (5 900kg).

## WEIGHT: BASIC MACHINE and COMPONENTS

### Basic Machine Weight and Overall width



Excluding front-end attachment, fuel, hydraulic oil, coolant, etc., and including counterweight.

#### ZX280-5G

| Shoe width | Weight    | Overall width |
|------------|-----------|---------------|
| 600 mm     | 21 300 kg | 3 190 mm      |
| 700 mm     | 21 900 kg | 3 290 mm      |
| 800 mm     | 22 300 kg | 3 390 mm      |
| 900 mm     | 22 600 kg | 3 490 mm      |

#### ZX280LC-5G

| Shoe width | Weight    | Overall width |
|------------|-----------|---------------|
| 600 mm     | 22 400 kg | 3 190 mm      |
| 700 mm     | 22 700 kg | 3 290 mm      |
| 800 mm     | 23 100 kg | 3 390 mm      |
| 900 mm     | 23 400 kg | 3 490 mm      |

### Component weights

|                                   | ZX280-5G / ZX280LC-5G |
|-----------------------------------|-----------------------|
| Counterweight                     | 5 900 kg              |
| Boom (with boom and arm cylinder) | 2 930 kg              |
| 2.42 m arm (with bucket cylinder) | 1 350 kg              |
| 3.11 m arm (with bucket cylinder) | 1 430 kg              |
| 3.76 m arm (with bucket cylinder) | 1 520 kg              |
| 1.10 m <sup>3</sup> bucket        | 900 kg                |

# SPECIFICATIONS

## BUCKET AND ARM DIGGING FORCES

| Arm length                       | 2.42 m              | 3.11 m              | 3.76 m              |
|----------------------------------|---------------------|---------------------|---------------------|
| Bucket digging force* ISO        | 202 kN (20 600 kgf) | 202 kN (20 600 kgf) | 202 kN (20 600 kgf) |
| Bucket digging force* SAE : PCSA | 175 kN (17 900 kgf) | 175 kN (17 900 kgf) | 175 kN (17 900 kgf) |
| Arm crowd force* ISO             | 182 kN (18 500 kgf) | 144 kN (14 700 kgf) | 126 kN (12 900 kgf) |
| Arm crowd force* SAE : PCSA      | 174 kN (17 700 kgf) | 138 kN (14 100 kgf) | 122 kN (12 400 kgf) |

\* At power boost

## BACKHOE ATTACHMENTS

Boom and arms are of welded, box-section design. 6.20 m boom, and 2.42 m, 3.11 m and 3.76 m arms are available. Bucket is of welded steel structure. Side clearance adjust mechanism provided on the bucket joint bracket.

### Buckets

| Capacity   | Width                |                   | No. Of teeth | Weight   | Recommendation |            |            |            |            |            |
|--|----------------------|-------------------|--------------|----------|----------------|------------|------------|------------|------------|------------|
|  | Without side cutters | With side cutters |              |          | ZX280-5G       |            |            | ZX280LC-5G |            |            |
| ISO heaped   |                      |                   |              |          | 2.42 m arm     | 3.11 m arm | 3.76 m arm | 2.42 m arm | 3.11 m arm | 3.76 m arm |
| 1.00 m <sup>3</sup>  | 1 130 mm             | 1 260 mm          | 5            | 850 kg   | ◎              | ◎          | ◎          | ◎          | ◎          | ◎          |
| 1.10 m <sup>3</sup>  | 1 220 mm             | 1 350 mm          | 5            | 900 kg   | ◎              | ◎          | ○          | ◎          | ◎          | ◎          |
| 1.40 m <sup>3</sup>  | 1 500 mm             | 1 630 mm          | 5            | 1 020 kg | ○              | ○          | —          | ○          | ○          | □          |
| 1.62 m <sup>3</sup>  | 1 700 mm             | 1 830 mm          | 5            | 1 080 kg | □              | —          | —          | □          | —          | —          |
| *1 0.92 m <sup>3</sup>   | 1 130 mm             | 1 180 mm          | 5            | 990 kg   | ●              | ●          | —          | ●          | ●          | —          |
| *2 1.10 m <sup>3</sup>   | 1 220 mm             | 1 350 mm          | 5            | 1 030 kg | ◎              | ◎          | ○          | ◎          | ◎          | ◎          |
| *2 1.40 m <sup>3</sup>   | 1 500 mm             | 1 630 mm          | 5            | 1 180 kg | ○              | ○          | —          | ○          | ○          | □          |
| *3 1.10 m <sup>3</sup>   | 1 230 mm             | 1 360 mm          | 5            | 1 030 kg | ◎              | ◎          | ○          | ◎          | ◎          | ◎          |
| *4 0.80 m <sup>3</sup>   | 1 000 mm             |                   | 3            | 1 220 kg | ●              | ●          | —          | ●          | ●          | —          |
| One-point ripper   |                      |                   | 1            | 680 kg   | ●              | ●          | —          | ●          | ●          | —          |
| Center-pull type clamshell bucket: 0.60 m <sup>3</sup> (CECE heaped), Width 940 mm |                      |                   | 8            | 1 130 kg | ◎              | ◎          | —          | ◎          | ◎          | —          |
| Shell-push type clamshell bucket: 0.80 m <sup>3</sup> (CECE heaped), Width 910 mm  |                      |                   | 9            | 1 360 kg | ◎              | ◎          | —          | ◎          | ◎          | —          |

\*1 Rock bucket

\*2 Reinforced bucket

\*3 Heavy-duty bucket

\*4 Ripper bucket

◎ Suitable for materials with density of 2 000 kg/m<sup>3</sup> or less

○ Suitable for materials with density of 1 600 kg/m<sup>3</sup> or less


□ Suitable for materials with density of 1 100 kg/m<sup>3</sup> or less

● Heavy-duty service

◇ Slope-finishing service

— Not applicable

## WORKING RANGES




| Arm length                            | 2.42 m | 3.11 m | 3.76 m |
|---------------------------------------|--------|--------|--------|
| A Max. digging reach                  | 10 060 | 10 710 | 11 270 |
| A' Max. digging reach (on ground)     | 9 860  | 10 520 | 11 090 |
| B Max. digging depth                  | 6 530  | 7 220  | 7 870  |
| B' Max. digging depth for 2.5 m level | 6 310  | 7 040  | 7 710  |
| C Max. cutting height                 | 9 910  | 10 270 | 10 470 |
| D Max. dumping height                 | 6 980  | 7 330  | 7 540  |
| D' Min. dumping height                | 3 450  | 2 740  | 2 090  |
| E Min. swing radius                   | 4 060  | 3 900  | 3 890  |
| F Max. vertical wall digging depth    | 5 650  | 6 480  | 7 050  |

Excluding track shoe lug

Unit: mm

# SPECIFICATIONS

## DIMENSIONS




Unit: mm

|  | ZX280-5G | ZX280LC-5G |
|--|----------|------------|
| A Distance between tumbler                 | 3 730    | 4 050      |
| B Undercarriage length                     | 4 670    | 4 940      |
| * C Counterweight clearance                | 1 170    | 1 170      |
| D Rear-end swing radius                    | 3 140    | 3 140      |
| D' Rear-end length                         | 3 140    | 3 140      |
| E Overall width of upperstructure          | 2 870    | 2 870      |
| F Overall height of cab                    | 3 110    | 3 110      |
| F' Overall height of upperstructure        | 3 180    | 3 180      |
| * G Min. ground clearance                  | 510      | 510        |
| H Track gauge                              | 2 590    | 2 590      |
| I Track shoe width                         | G 600    | G 600      |
| J Undercarriage width                      | 3 190    | 3 190      |
| K Overall width                            | 3 190    | 3 190      |
| * L Track height with triple grouser shoes | 1 070    | 1 070      |
| M Overall length                           |          |            |
| With 2.42 m arm                            | 10 640   | 10 640     |
| With 3.11 m arm                            | 10 550   | 10 550     |
| With 3.76 m arm                            | 10 600   | 10 600     |
| N Overall height of boom                   |          |            |
| With 2.42 m arm                            | 3 410    | 3 410      |
| With 3.11 m arm                            | 3 170    | 3 170      |
| With 3.76 m arm                            | 3 310    | 3 310      |

\* Excluding track shoe lug G: Triple grouser shoe

# LIFTING CAPACITIES (Without Bucket)

- Notes: 1. Ratings are based on ISO 10567.  
 2. Lifting capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.  
 3. The load point is the center-line of the bucket pivot mounting pin on the arm.  
 4. \*Indicates load limited by hydraulic capacity.  
 5. 0 m = Ground.



For lifting capacities, subtract bucket and quick hitch weight from lifting capacities without bucket.

## ZX280-5G

Rating over-front Rating over-side or 360 degrees Unit : kg

| Conditions   | Load point height m | Load radius m     |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | At max. reach     |                                 |       |       |        |        |       |      |
|--|---------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------|-------|--------|--------|-------|------|
|  |                     | 1.5               |                                 | 3.0               |                                 | 4.5               |                                 | 6.0               |                                 | 7.5               |                                 | 9.0               |                                 | meter |       |        |        |       |      |
|  |                     | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | meter | meter | meter  |        |       |      |
| Boom 6.20 m<br>Arm 2.42 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 6.0                 |                   |                                 |                   |                                 |                   |                                 | *8 040            | 7 650                           |                   |                                 |                   |                                 |       |       | 7 570  | 5 360  | 7.46  |      |
|  | 4.5                 |                   |                                 |                   |                                 | *11 280           | *11 280                         | *9 040            | 7 340                           | 7 400             | 5 220                           |                   |                                 |       |       | 6 530  | 4 600  | 8.11  |      |
|  | 3.0                 |                   |                                 |                   |                                 | *14 220           | 10 430                          | 6 950             | 7 220                           | 5 050             |                                 |                   |                                 |       |       | 6 030  | 4 220  | 8.44  |      |
|  | 1.5                 |                   |                                 |                   |                                 |                   |                                 | 9 760             | 6 630                           | 7 030             | 4 880                           |                   |                                 |       |       | 5 880  | 4 100  | 8.49  |      |
|  | 0 (Ground)          |                   |                                 |                   |                                 |                   |                                 | 15 150            | 9 680                           | 9 560             | 6 440                           | 6 920             | 4 770                           |       |       | 6 040  | 4 190  | 8.27  |      |
|  | -1.5                |                   |                                 |                   |                                 |                   |                                 | *10 350           | *10 350                         | 15 180            | 9 700                           | 9 510             | 6 400                           | 6 900 | 4 760 |        | 6 610  | 4 570 | 7.75 |
|  | -3.0                |                   |                                 |                   |                                 |                   |                                 | *18 920           | *18 920                         | *14 320           | 9 860                           | 9 620             | 6 490                           |       |       | 7 950  | 5 460  | 6.86  |      |
|  | -4.5                |                   |                                 |                   |                                 |                   |                                 | *14 680           | *14 680                         | *11 190           | 10 220                          |                   |                                 |       |       | *9 010 | 7 820  | 5.42  |      |
|  | -6.0                |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |       |       |        |        |       |      |
| Boom 6.20 m<br>Arm 3.11 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 6.0                 |                   |                                 |                   |                                 |                   |                                 | *7 140            | *7 140                          | *6 960            | 5 440                           |                   |                                 |       |       | *4 740 | 4 660  | 8.19  |      |
|  | 4.5                 |                   |                                 |                   |                                 | *9 840            | *9 840                          | *8 200            | 7 490                           | *7 400            | 5 300                           |                   |                                 |       |       | *4 730 | 4 080  | 8.78  |      |
|  | 3.0                 |                   |                                 |                   |                                 | *12 820           | 10 790                          | *9 610            | 7 080                           | 7 280             | 5 100                           | 5 480             | 3 840                           |       |       | *4 890 | 3 780  | 9.09  |      |
|  | 1.5                 |                   |                                 |                   |                                 | *15 230           | 10 050                          | 9 860             | 6 700                           | 7 060             | 4 900                           | 5 390             | 3 750                           |       |       | *5 220 | 3 670  | 9.14  |      |
|  | 0 (Ground)          |                   |                                 |                   |                                 |                   |                                 | 15 180            | 9 700                           | 9 580             | 6 450                           | 4 750             |                                 |       |       | 5 380  | 3 730  | 8.93  |      |
|  | -1.5                | *6 820            | *6 820                          | *10 250           | *10 250                         | 15 090            | 9 620                           | 9 460             | 6 340                           | 6 830             | 4 680                           |                   |                                 |       |       | 5 790  | 4 010  | 8.45  |      |
|  | -3.0                | *11 900           | *11 900                         | *16 480           | *16 480                         | 15 190            | 9 700                           | 9 490             | 6 370                           | 6 880             | 4 730                           |                   |                                 |       |       | 6 710  | 4 620  | 7.65  |      |
|  | -4.5                |                   |                                 | *17 660           | *17 660                         | *12 950           | 9 960                           | *9 560            | 6 570                           |                   |                                 |                   |                                 |       |       | *8 660 | 6 050  | 6.39  |      |
|  | -6.0                |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |       |       |        |        |       |      |
| Boom 6.20 m<br>Arm 3.76 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 7.5                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | *5 160            | *5 160                          |                   |                                 |       |       | *3 950 | *3 950 | 7.94  |      |
|  | 6.0                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | *6 240            | 5 540                           |                   |                                 |       |       | *3 810 | *3 810 | 8.82  |      |
|  | 4.5                 |                   |                                 |                   |                                 |                   |                                 | *7 360            | *7 360                          | *6 780            | 5 380                           | *5 250            | 3 980                           |       |       | *3 820 | 3 700  | 9.37  |      |
|  | 3.0                 |                   |                                 |                   |                                 | *11 420           | 11 130                          | *8 830            | 7 210                           | 7 350             | 5 150                           | 5 520             | 3 870                           |       |       | *3 950 | 3 440  | 9.66  |      |
|  | 1.5                 |                   |                                 |                   |                                 | *14 210           | 10 260                          | 9 960             | 6 790                           | 7 100             | 4 930                           | 5 390             | 3 750                           |       |       | *4 200 | 3 340  | 9.70  |      |
|  | 0 (Ground)          |                   |                                 |                   |                                 | *6 510            | *6 510                          | 15 250            | 9 750                           | 9 610             | 6 470                           | 6 900             | 4 740                           | 5 290 | 3 660 | *4 640 | 3 380  | 9.51  |      |
|  | -1.5                | *6 480            | *6 480                          | *9 930            | *9 930                          | 15 020            | 9 550                           | 9 420             | 6 300                           | 6 780             | 4 630                           | 5 250             | 3 620                           |       |       | 5 200  | 3 590  | 9.06  |      |
|  | -3.0                | *10 280           | *10 280                         | *14 500           | *14 500                         | 15 030            | 9 560                           | 9 380             | 6 270                           | 6 770             | 4 620                           |                   |                                 |       |       | 5 880  | 4 050  | 8.32  |      |
|  | -4.5                | *14 880           | *14 880                         | *19 910           | 19 610                          | *14 100           | 9 740                           | 9 510             | 6 380                           |                   |                                 |                   |                                 |       |       | 7 340  | 5 030  | 7.18  |      |
|  | -6.0                |                   |                                 | *14 650           | *14 650                         | *10 530           | 10 150                          |                   |                                 |                   |                                 |                   |                                 |       |       | *8 380 | 7 760  | 5.41  |      |

## ZX280LC-5G

Rating over-front Rating over-side or 360 degrees Unit : kg

| Conditions   | Load point height m | Load radius m     |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | At max. reach     |                                 |       |       |        |        |      |
|--|---------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------------------|---------------------------------|-------|-------|--------|--------|------|
|  |                     | 1.5               |                                 | 3.0               |                                 | 4.5               |                                 | 6.0               |                                 | 7.5               |                                 | 9.0               |                                 | meter |       |        |        |      |
|  |                     | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | Rating over-front | Rating over-side or 360 degrees | meter | meter | meter  |        |      |
| Boom 6.20 m<br>Arm 2.42 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 6.0                 |                   |                                 |                   |                                 |                   |                                 | *8 040            | 7 800                           |                   |                                 |                   |                                 |       |       | *7 900 | 5 470  | 7.46 |
|  | 4.5                 |                   |                                 |                   |                                 | *11 280           | *11 280                         | *9 040            | 7 490                           | 8 050             | 5 330                           |                   |                                 |       |       | 7 390  | 4 700  | 8.11 |
|  | 3.0                 |                   |                                 |                   |                                 | *14 220           | 10 640                          | *10 340           | 7 100                           | 6 830             | 5 160                           |                   |                                 |       |       | 6 830  | 4 320  | 8.44 |
|  | 1.5                 |                   |                                 |                   |                                 |                   |                                 | 11 210            | 6 770                           | 8 010             | 4 990                           |                   |                                 |       |       | 6 670  | 4 190  | 8.49 |
|  | 0 (Ground)          |                   |                                 |                   |                                 | *16 230           | 9 900                           | 11 000            | 6 590                           | 6 590             | 4 880                           |                   |                                 |       |       | 6 870  | 4 290  | 8.27 |
|  | -1.5                |                   |                                 |                   |                                 | *10 350           | *10 350                         | *15 820           | 9 920                           | 10 950            | 6 540                           | 7 870             | 4 870                           |       |       | 7 530  | 4 680  | 7.75 |
|  | -3.0                |                   |                                 |                   |                                 | *18 920           | *18 920                         | *14 320           | 10 080                          | *10 890           | 6 640                           |                   |                                 |       |       | 9 080  | 5 580  | 6.86 |
|  | -4.5                |                   |                                 |                   |                                 | *14 680           | *14 680                         | *11 190           | 10 430                          |                   |                                 |                   |                                 |       |       | *9 010 | 7 990  | 5.42 |
|  | -6.0                |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |       |       |        |        |      |
| Boom 6.20 m<br>Arm 3.11 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 6.0                 |                   |                                 |                   |                                 |                   |                                 | *7 140            | *7 140                          | *6 960            | 5 550                           |                   |                                 |       |       | *4 740 | *4 740 | 8.19 |
|  | 4.5                 |                   |                                 |                   |                                 | *9 840            | *9 840                          | *8 200            | 7 640                           | *7 400            | 5 410                           |                   |                                 |       |       | *4 730 | 4 170  | 8.78 |
|  | 3.0                 |                   |                                 |                   |                                 | *12 820           | 11 000                          | *9 610            | 7 230                           | *8 100            | 5 210                           | 5 570             | 3 930                           |       |       | *4 890 | 3 870  | 9.09 |
|  | 1.5                 |                   |                                 |                   |                                 | *15 230           | 10 260                          | *10 920           | 6 850                           | 8 040             | 5 010                           | 6 110             | 3 840                           |       |       | *5 220 | 3 760  | 9.14 |
|  | 0 (Ground)          |                   |                                 |                   |                                 | *16 280           | 9 920                           | 11 020            | 6 600                           | 7 870             | 4 860                           |                   |                                 |       |       | *5 800 | 3 820  | 8.93 |
|  | -1.5                | *6 820            | *6 820                          | *10 250           | *10 250                         | *16 210           | 9 830                           | 10 900            | 6 490                           | 7 800             | 4 790                           |                   |                                 |       |       | 6 590  | 4 100  | 8.45 |
|  | -3.0                | *11 900           | *11 900                         | *16 480           | *16 480                         | *15 200           | 9 920                           | 10 930            | 6 520                           | 7 850             | 4 840                           |                   |                                 |       |       | 7 650  | 4 730  | 7.65 |
|  | -4.5                |                   |                                 | *17 660           | 17 660                          | *12 950           | 10 170                          | *9 560            | 6 720                           |                   |                                 |                   |                                 |       |       | *8 660 | 6 190  | 6.39 |
|  | -6.0                |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 |       |       |        |        |      |
| Boom 6.20 m<br>Arm 3.76 m<br>Counterweight 5 900 kg<br>Shoe 600 mm | 7.5                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | *5 160            | *5 160                          |                   |                                 |       |       | *3 950 | *3 950 | 7.94 |
|  | 6.0                 |                   |                                 |                   |                                 |                   |                                 |                   |                                 | *6 240            | 5 650                           |                   |                                 |       |       | *3 810 | *3 810 | 8.82 |
|  | 4.5                 |                   |                                 |                   |                                 |                   |                                 | *7 360            | *7 360                          | *6 780            | 5 490                           | *5 250            | 4 070                           |       |       | *3 820 | 3 790  | 9.37 |
|  | 3.0                 |                   |                                 |                   |                                 | *11 420           | 11 340                          | *8 830            | 7 360                           | *7 560            | 5 270                           | 6 250             | 3 960                           |       |       | *3 950 | 3 530  | 9.66 |
|  | 1.5                 |                   |                                 |                   |                                 | *14 210           | 10 470                          | *10 310           | 6 930                           | 8 070             | 5 040                           | 6 120             | 3 840                           |       |       | *4 200 | 3 420  | 9.70 |
|  | 0 (Ground)          |                   |                                 |                   |                                 | *6 510            | *6 510                          | *15 830           | 9 970                           | 11 060            | 6 620                           | 7 870             | 4 850                           | 6 010 | 3 750 | *4 640 | 3 460  | 9.51 |
|  | -1.5                | *6 480            | *6 480                          | *9 930            | *9 930                          | *16 270           | 9 770                           | 10 860            | 6 450                           | 7 750             | 4 740                           | *5 880            | 3 710                           |       |       | *5 360 | 3 670  | 9.06 |
|  | -3.0                | *10 280           | *10 280                         | *14 500           | *14 500                         | *15 740           | 9 780                           | 10 820            | 6 420                           | 7 740             | 4 730                           |                   |                                 |       |       | *6 650 | 4 140  | 8.32 |
|  | -4.5                | *14 880           | *14 880                         | *19 910           | 19 910                          | *14 100           | 9 960                           | *10 550           | 6 530                           |                   |                                 |                   |                                 |       |       | *8 280 | 5 150  | 7.18 |
|  | -6.0                |                   |                                 | *14 650           | *14 650                         | *10 530           | 10 370                          |                   |                                 |                   |                                 |                   |                                 |       |       | *8 380 | 7 930  | 5.41 |

Standard and optional equipment may vary by country, so please consult your Hitachi dealer for details.

● : Standard equipment      ○ : Optional equipment

|  | ZX280-5G / ZX280LC-5G |
|--|-----------------------|
| <b>ENGINE</b>  |                       |
| Air cleaner double filters   | ●                     |
| Auto idle system   | ●                     |
| Cartridge-type engine oil filter   | ●                     |
| Cartridge-type fuel pre-filter   | ●                     |
| Cartridge-type fuel main filter  | ●                     |
| Dry-type air filter with evacuator valve (with air filter restriction indicator) | ●                     |
| ECO/PWR mode control   | ●                     |
| Engine warm-up device  | ●                     |
| Fan guard  | ●                     |
| Water separator  | ●                     |
| Pre-cleaner  | ○                     |
| Dust-Proof indoor net  | ●                     |
| Radiator reserve tank  | ●                     |
| 50 A alternator  | ●                     |

| <b>HYDRAULIC SYSTEM</b>                               |   |
|---|---|
| Auto power lift                                       | ● |
| Control valve with main relief valve                  | ● |
| Full-flow filter                                      | ● |
| High mesh full flow filter with restriction indicator | ○ |
| Pilot filter  | ● |
| Power boost   | ● |
| Suction filter  | ● |
| One extra port for control valve                      | ● |
| Work mode selector                                    | ● |

|  | ZX280-5G / ZX280LC-5G |
|--|-----------------------|
| <b>CAB</b>   |                       |
| All-weather sound suppressed steel cab   | ●                     |
| AM-FM radio with 2 speaker   | ●                     |
| Ashtray  | ●                     |
| Auto control air conditioner   | ●                     |
| AUX. terminal and storage  | ○                     |
| Cab (Center pillar reinforced structure)   | ●                     |
| Drink holder   | ●                     |
| Drink holder with hot & cool   | ●                     |
| Electric double horn   | ●                     |
| Engine shut-off lever  | ●                     |
| Evacuation hammer  | ●                     |
| Fire extinguisher bracket  | ○                     |
| Floor mat  | ●                     |
| Footrest   | ●                     |
| Front window washer  | ●                     |
| Front windows on upper, lower and left side can be opened                        | ●                     |
| Lower cab front guard  | ○                     |
| Upper cab front guard  | ○                     |
| Glove compartment  | ●                     |
| Hot & cool box   | ●                     |
| Intermittent windshield wipers   | ●                     |
| Key cylinder light   | ●                     |
| LED room light with door courtesy  | ●                     |
| OPG top guard Level I (ISO10262) compliant cab                                   | ●                     |
| Pilot control shut-off lever   | ●                     |
| Rear tray  | ●                     |
| Retractable seat belt  | ●                     |
| Rubber radio antenna   | ●                     |
| Seat : mechanical suspension seat  | ○                     |
| Seat : air suspension seat with heater   | ○                     |
| Seat adjustment part : backrest, armrest, height and angle, slide forward / back | ●                     |
| Short wrist control levers   | ●                     |
| 4 fluid-filled elastic mounts  | ●                     |
| 24V cigarette lighter  | ●                     |

|  | ZX280-5G / ZX280LC-5G |
|--|-----------------------|
| <b>MONITOR SYSTEM</b>  |                       |
| Alarm buzzers: overheating, engine oil pressure  | ●                     |
| Alarms: overheating, engine warning, engine oil pressure, alternator, minimum fuel level, hydraulic filter restriction, air filter restriction, work mode, etc | ●                     |
| Display of meters: water temperature, hour, fuel rate, clock   | ●                     |
| Other displays: work mode, auto-idle, glow, rearview monitor, operating conditions, etc  | ●                     |
| 32 languages selection   | ●                     |

| <b>LIGHTS</b>                    |   |
|----------------------------------|---|
| Additional cab roof front lights | ○ |
| Additional boom light with cover | ○ |
| 2 working lights                 | ● |

| <b>UPPER STRUCTURE</b>               |   |
|--------------------------------------|---|
| Electric fuel refilling pump         | ○ |
| Fuel level float                     | ● |
| Hydraulic oil level gauge            | ● |
| Rear view camera                     | ○ |
| Rear view mirror (right & left side) | ● |
| Swing parking brake                  | ● |
| Tool box                             | ● |
| Undercover                           | ● |
| 6.0 mm reinforced undercover         | ○ |
| Utility space                        | ● |
| 5 900 kg counterweight               | ● |
| 2 x 88 Ah batteries                  | ● |

|  | ZX280-5G / ZX280LC-5G |
|--|-----------------------|
| <b>UNDERCARRIAGE</b>                                 |                       |
| Bolt-on sprocket                                     | ●                     |
| Reinforced track links with pin seals                | ●                     |
| Travel motor covers                                  | ●                     |
| Travel parking brake                                 | ●                     |
| 9.0 mm reinforced track undercover                   | ○                     |
| Track guard (each side) and hydraulic track adjuster | ●                     |
| Upper and lower rollers                              | ●                     |
| 3 track guards                                       | ○                     |
| 4 tie down hooks                                     | ●                     |
| 600 mm triple grouser shoes                          | ●                     |

| <b>FRONT ATTACHMENTS</b>                |   |
|---|---|
| Centralized lubrication system          | ● |
| Dirt seal on all bucket pins            | ● |
| Flanged pin                             | ● |
| HN bushing                              | ● |
| Reinforced resin thrust plate           | ● |
| WC (tungsten-carbide) thermal spraying  | ● |
| 1.10 m <sup>3</sup> bucket (ISO heaped) | ● |
| 3.11 m arm                              | ● |
| 6.20 m boom                             | ● |

| <b>ATTACHMENTS</b>                                    |   |
|---|---|
| Attachment basic piping                               | ○ |
| Breaker and crusher piping                            | ○ |
| High mesh full flow filter with restriction indicator | ○ |
| Parts for breaker and crusher                         | ○ |
| 2 pump combined flow for attachment basic piping      | ○ |
| Line filter   | ○ |

| <b>MISCELLANEOUS</b>                       |   |
|--|---|
| Lockable fuel refilling cap                | ● |
| Lockable machine covers                    | ● |
| Onboard information controller             | ● |
| Skid-resistant tapes, plates and handrails | ● |
| Standard tool kit                          | ● |
| Travel direction mark on track frame       | ● |
| Global e-Service                           | ● |





**Built on the foundation of superb technological capabilities, Hitachi Construction Machinery is committed to providing leading-edge solutions and services to contribute as a reliable partner to the business of customers worldwide.**

## Hitachi Environmental Vision 2050

Our Environmental Vision envisions a low-carbon society; a resource efficient society; a harmonized society with nature. To achieve such a sustainable society, we have established a set of long-term environmental targets called Hitachi Environmental Innovation 2050.

### Reducing Environmental Impact by New ZAXIS

Hitachi makes a green way to cut carbon emissions for global warming prevention according to LCA\*. New ZAXIS utilizes lots of technological advances, including the new ECO mode, and Isochronous Control. Hitachi has long been committed to recycling of components, such as aluminum parts in radiators and oil cooler. Resin parts are marked for recycling.

\*Life Cycle Assessment – ISO 14040

Before using a machine with a satellite communication system, please make sure that the satellite communication system complies with local regulations, safety standards and legal requirements. If not so, please make modifications accordingly.

These specifications are subject to change without notice. Illustrations and photos show the standard models, and may or may not include optional equipment, accessories, and all standard equipment with some differences in color and features. Before use, read and understand the Operator's Manual for proper operation.